



Features

General

■ Operating frequency (HF)	13.56 MHz
■ Operating frequency (LF)	125KHz
■ Transponders (HF)	ISO15693/ISO14443 / I-CODE/ Mirare
■ Transponders (LF)	Unique/H4102/EM4200/ TK5557/TK5567/ Q5
■ RF transmitting power	100mW
■ Approx. read range (LF)	*max 12 cm
■ Approx. read range (HF)	*max 6 cm
■ TCP/IP Connection	10/100MHz
■	Sure Connection™
■	RJ45 Connector
■ Digital Input	2 Galvanic Isolation
■ Digital Output	2 Relay
■ Beeper	Integrated
■ Power	12/24V DC/AC
■ Current consumption	max. 300 mA
■ Real Time Clock with battery backup	
■ Operation modes	Polling-Mode & Scan Mode
■ Optical indicators	
LCD	2x16 characters
LED	Green Power/Status
	Red Action
■ Driver Support	
- Windows XP/VISTA 32 Bit	
- Windows DLLs, API and PC driver available	
* Using ISO TAG	

RoHS

(Fully RoHS (2002/95/CE) Compliant).

WALLY has been designed to be easily wall mounted in both indoor and outdoor environments.

Its compact size, the flexibility of TCP/IP connection, the possibility to show information on a High brightness 16 x 2 LCD Display, the presence of optoisolated inputs and relay outputs, the high-speed writing/reading performance, the security guaranteed with all transactions, all allow a flexible use on various applications.

The possibility of remote maintenance of the system, together with software updates possible through the same network connection reduce management costs by increasing the reliability of the system while allowing higher operating efficiency.

WALLY

Benefits

Front panel 20° incline
Sure Connection™
Easy to wall Installation
Multifunctionality

Mechanical and Electrical informations

Dimension	135 x 190 x 37mm
Wall Moaunt Base	49 x 49 x 22mm
Housing	ABS
Color	off-white RAL 9002
Weight	<gr. 400
Protection class	IP54
Supply voltage	12 – 24V DC/AC
Current	300mA @ 12V
Temperature range	
Operation	0 °C up to 50 °C
Storage	-40 °C up to 85 °C
Relative air humidity	95% (non-condensing)

Options

Optoisolated Inputs

Accessories

Order Code

WL-LH-001	WALLY 125KHz – 13.56MHz Standard w/ LCD
WL-LH-002	WALLY 125KHz – 13.56MHz w/o LCD

IT IS POSSIBLE TO MOVE FROM STANDARD TO INDIVIDUAL SOLUTIONS WITH OUR "COMPREHENSIVE SERVICES".

CONTACT US FOR ANY FURTHER DETAILS ON THIS.

About Us

TechSigno srl is an independent company that build RFID system and intelligent objects for multimedia, industrial, transportation, medical, and wireless applications. Working closely with our customers, we meet the specific made-to-order demands of our customer to achieve maximum functionality, efficiency, reliability and therefore satisfaction.

AUTHORIZED DISTRIBUTOR

Note:

The information in this document is subject to change without notice and should not be construed as a commitment by TechSigno srl. All reasonable precautions have been taken, TechSigno srl assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective compagnie.



Ver. 1.2 En

TechSigno S.r.l.

Via dei Boschi 2/13, - 33040 Pradamano UD - ITALY - tel.: +39.0432.603604 - fax: +39.0432.602905 - e-mail: info@techsigno.com



www.techsigno.com