

FEATURES

General

■ Operating frequency (HF)	13.56 MHz
■ Operating frequency (LF)	125KHz
■ Transponder (HF)	ISO14443/A
	Mifare
	Felica
■ Transponders (LF)	Unique
	H4100 - H4102 – EM4100 – EM4102 – EM4200
	TK5557 – TK5567 Read Only Codified
■ Approx. read range (LF/HF)	5 cm depending on tag antenna size
■ Interface	USB 2.0 RS232 Optionally
■ Communication Protocols	USB Keyboard
■ Power	Cable 5V USB power Single Cell AAA 1.5V Battery
■ Current consumption	max. 200 mA
■ Operation modes	Scan Mode White List Association
■ Antenna	Integrated
■ Optical indicators	1 Red/Green LED Battery Status and Reader Status LCD 101 x 67 dots
■ Driver Support	- Windows XP/VISTA 32 Bit - Windows DLLs, API and PC driver available

RoHS

(Fully RoHS (2002/95/CE) Compliant).



TechSigno uSCAN è un lettore RFID portatile con LCD e Real Time Clock integrato. Ideale per applicazioni di data collection.

uSCAN è in grado di leggere TAG RFID a 125KHz o 13.56MHz in qualsiasi momento ed in qualsiasi luogo senza la necessità di un collegamento ad un computer.

Il dato letto dal TAG RFID è visualizzato sul display LCD viene registrato nella memoria interna con l'indicazione di data ed ora della lettura pronto per essere scaricato sul computer tramite l'interfaccia USB.

Le caratteristiche del **uSCAN** sono:

- 512K bytes Memory
- Real Time Clock (RTC) integrato
- Piccole dimensioni
- Lettura di 125KHz o 13.56MHz RFID TAG
- LCD display (101 x 67 dots)
- Auto spegnimento
- Indicatore di Batteria scarica
- Indicatore di Memoria Piena
- White List

Le applicazioni tipiche sono:

- Rilevamento Presenze
- Raccolta dati Visitatori Fiere
- Raccolta dati Partecipanti Conferenze
- Sistema di monitoraggio Guardie
- Raccolta dati presenza studenti

Benefits

Compact dimensions
Powered by Single Cell AAA 1.5V Battery
Easy to Use
LCD Display 101 x 67
512Kb Memory size for up to 8192 Records
Auto Off for power saving
White List

Mechanical and Electrical informations

Dimension	58 x 47 x 20
Housing	ABS
Color	off-white RAL 9002
Weight	<gr. 200
Protection class	IP40
Supply voltage	Cable 5V DC USB Single Cell AAA 1.5V Battery
Current	200mA
Temperature range	
Operation	0 °C up to 55 °C
Storage	-40 °C up to 85 °C
Relative air humidity	90% (non-condensing)

Options

Reader with RS232 Communication Port

Accessories

Order Code

USCAN-L01W	125KHz USB Reader with white list
USCAN-L02W	13.56MHZ USB Reader with white list

IT IS POSSIBLE TO MOVE FROM STANDARD TO INDIVIDUAL SOLUTIONS WITH OUR "COMPREHENSIVE SERVICES".

CONTACT US FOR ANY FURTHER DETAILS ON THIS.

About Us

TechSigno srl is an independent company that build RFID system and intelligent objects for multimedia, industrial, transportation, medical, and wireless applications. Working closely with our customers, we meet the specific made-to-order demands of our customer to achieve maximum functionality, efficiency, reliability and therefore satisfaction.

AUTHORIZED DISTRIBUTOR

Note:

The information in this document is subject to change without notice and should not be construed as a commitment by TechSigno srl. All reasonable precautions have been taken, TechSigno srl assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective compagnie.



Ver. 1.0 IT

TechSigno S.r.l.

Via Selvuzzis, 53 - 33100 Udine - ITALY - tel.: +39.0432.603604 - fax: +39.0432.602905 - e-mail: info@techsigno.com

